



## 30W Interchangeable Plug Series



Interchangeable clips sold separately

### Features

- Limited Power Source
- Level VI Efficiency Compliance
- Class II Double Insulated
- Class B EMI

### Applications

- Peripherals
- Gaming Machines
- Point of Sale Equipment
- Network Equipment

### Safety Approvals

- cUL/UL
- CE
- RCM

### Mechanical Characteristics

- Length: 82.7mm (3.26in)
- Width: 55mm (2.17in)
- Height: 39.1mm (1.54in)
- Weight: 180g (6.35oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple P-P (max.)	Regulation	
		Min.	Max.		Line	Load
PSAA30R-120	12V	0A	2.50A	120mV	±5%	
PSAA30R-150	15V	0A	2.00A	200mV	±5%	
PSAA30R-240	24V	0A	1.25A	240mV	±5%	
PSAA30R-560	56V	0A	5.36A	560mV	±5%	

- (1) Measured with by-pass capacitors 0.1uF/10uF at output connector terminal and oscilloscope set at 20MHz.
- (2) At no load to full load, 1.5 meter (approx 5ft) DC cord, measured at the plug

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:****AC Input Voltage Rating**

100 to 240V AC

**AC Input Voltage Range**

90 to 264V AC

**AC Input Frequency**

47 to 63Hz

**Input Current**

0.8A (RMS) maximum at 120V AC

0.5A (RMS) maximum at 240V AC

**Leakage Current**

0.25mA maximum

**Inrush Current**

&lt;60A for 100V AC at maximum load

&lt;100A for 240V AC at maximum load

(Cold start at ambient 25°C)

**Input Power Saving**

&lt;0.1W Max. @ 0A 230Vac 50Hz

**OUTPUT:****Efficiency**

DOE Level VI

**ENVIRONMENTAL****Temperature**

Operation 0 to +40°C

Non-operation -25 to +75°C

Humidity 20 to 90%

**Emissions**

FCC Class B

EN55022 Class B

**Immunity**

IEC61000-4-2 Level 4

IEC61000-4-3 Level 2

IEC61000-4-4 Level 2

IEC61000-4-5 Level 2

IEC61000-4-6 Level 2

IEC61000-4-8 Level 1

IEC61000-4-11

EN61000-3-2

**FEATURES:****Over-Voltage Protection**

Auto restart

**Over-Current Protection**

Auto-restart without damage

**Short-Circuit Protection**

Output can be shorted without damage

**Dielectric Withstand (Hi-pot) Test**

Input to Output: 3000V AC for 1 min., 10mA

**Insulation Resistance**

Input to output: 7M ohm, 500V DC

**DC Output Connector (Barrel Type)**

2.1 x 5.5 x 9.5mm Center Positive Standard

**AC Input Clips (sold separately)**

RPA – US

RPB – Brazil

RPC – China

RPE – Europe

RPH – Korea

RPI – India

RPK – UK

RPN – Argentina

RPS – Australia

RPX – IEC320 C8

PSAA30R

Dimension Diagram Unit: mm (inch)

